

# Swingblade® Exit

## Sophisticated Surface Mounted Exit



Swingblade® in wall mounted configuration



Swingblade® in ceiling mounted configuration

- One box solution complete with "EXIT" and "Pictograph" diffuser inserts for all diffuser combinations.
- "Edgelit" exit with rotating "Swingblade®" exit diffuser.
- Surface mounted exit that compliments the Ultrablade® exit.
- Energy efficient and low maintenance 50,000 hour cold cathode lamp.
- Separate mounting bracket for fast wall or ceiling installation.
- Single point, Clever-test® or Zoneworks® computerised testing options available.

### ONE BOX: BOTH STANDARDS



All these inserts come standard with each Swingblade®.

## High technology and good looks...

Clevertronics has combined a number of key design features and technologies to create the unique Swingblade® exit.

The sophisticated good looks of the Swingblade® match modern architectural styling while being easy to install and maintain. A separate mounting bracket means the Swingblade® is quick and easy to install. That combined with its strong low profile, extruded aluminum body and smart design help to provide the Swingblade® with a long service life.

Swingblade® uses proven energy and lumen efficient cold

cathode lamp technology combined with a unique rotating light bar and flat panel diffuser assembly.

The drop-in legend inserts are secured by a patented tamper proof legend cover.

All diffuser combinations of single-sided or double-sided, with or without arrows, "EXIT" or "Pictograph" options can be configured on site from the one box.

Clevertronics Swingblade® exits are available as single point units (SPU), Clever-test® or Zoneworks® computer monitoring options.

# Swingblade® Exit

## DIMENSIONS (mm)



Swingblade® comes standard with a universal slide-connect base for quick installation and maintenance.



## ORDERING INFORMATION

Detailed specification details available for download from Clevertronics website.

SWINGBLADE EXIT	TESTING OPTIONS			PHOTOMETRICS	
	Description	Standard	Clever-test®	Zoneworks®	C0
1x 4W CCFL Maintained	PSB4	DSB4	ZSB4	E1.25	C1.25

## SPACING TABLE

Detailed specification details available for download from Clevertronics website.

Classification	MOUNTING HEIGHTS (m)			
	2.1m	2.4m	2.7m	3m*
C1.25	3.2	3.1	2.8	2.4
E1.25	4.2	4.2	4	3.6

\* For mounting height restrictions please refer to AS2293.1

## Swingblade® features

- Patented industry first, tamper-proof "legend cover" for directional safety signage.
- Unique drop-in legend sheets make changing from "EXIT" to new "Pictograph" a simple task.
- Single-sided or double-sided wall or ceiling, and all directional options supplied as standard in one box.
- Energy and lumen efficient 50,000 hour cold cathode lamp standard.
- Separate fast connect mounting bracket for wall or ceiling installation.
- Large terminal blocks and cable entry hole minimises installation fuss.
- Quality extruded aluminum luminaire body and diffuser carriage.
- High integrity 70°C Nickel Cadmium battery pack.

## Clevertronics unique ONE BOX: BOTH STANDARDS solution

One box is all you will ever need regardless of what standard you require!

Each of our "ONE BOX: BOTH STANDARDS" exits comes with all the "EXIT" and "Pictograph" inserts all in the box.

One exit, one part number, one price, just open the box and PICK, SLIP AND CLIP.



1. Pick the correct decal



2. Slip it in



3. Clip it shut